

1145 MAGNETIC SWIPE READER FOR THE MOTOROLA ET1 TABLET

ENCRYPTED MAGNETIC SWIPE READER











A Compact and Convenient Solution

The 1145 Magnetic Swipe Reader is a compact screw-on peripheral for the Motorola ET1 Tablet. It's 3 track Encrypted Magnetic Card Reader allows magnetic stripe data to be read accurately and decoded in a secure, encrypted format.

Applications:

- Payment Applications
- Public Transportation Terminals
- Customer Loyalty
- Time and Attendance
- Network Access Control
- Automatic Fare Collection

Advanced Encryption

The 1145 Magnetic Swipe Reader incorporates cutting-edge hardware and encryption methods which allow the electronics to be embedded within the read head. The 1145 MSR not only performs the magnetic stripe data decoding, it also contains a microprocessor that handles encryption and communications.

The 1145 MSR reader supports ANSI, ISO, AAMVA, CA DMV and user-configurable generic formats.

The built-in encryption engine supports DES, TDES, and AES encryption with DUKPT key management. The information can be encrypted before leaving the read head, making this a perfect solution for applications requiring increased levels of security.

Features:

Security of data

The Encrypted Magnetic Card Reader has a built-in encryption engine utilizing DES, Triple DES and AES Encryption as well as DUKPT key management

Built for tough environments

The rugged design of the 1145 MSR means that it can withstand multiple drops of up to 1.2m whilst attached to the ET1 tablet

Simplicity

The reader is powered by the ET1 tablet making it an easy one piece, one charge solution. Existing ET1 accessories such as the hand strap can be used with the reader attached

Android

The open and flexible nature of the Android environment means developers can harness the power of the 1145 MSR hardware to create applications tailored to the end user's needs

SPECIFICATIONS

Physical Characteristics

Dimensions (WxLxH):	5.67 x 3.93 x 2.70 cm (2.23 x1.55 x 1.06 in.)
Weight:	28g (1oz)
Mechanical attachment:	Screw-on action
Docking:	Attachment maintains dockability with Motorola docking cradle for charging and syncing
Power:	Peripheral powered by Motorola ET1 tablet

Magnetic Card Reader

Format:	ANSI, ISO, AAMVA, CA DMV, user- configurable generic format
Swipe Speed:	127 to 1270 mm (5 to 50 in.) / sec, bi- directional
Decoders:	Generic, Raw Data
Track Reading Capabilities:	Tracks 1 and 3: 210 bpi Track 2: 75 and 210 bpi, autodetect
Connection:	Via ET1 USB host port for power and communication
Security:	Built-in encryption engine DES, Triple DES and AES Encryption DUKPT key management In-head electronics to prevent tampering

Environmental

Operating Temp.:	0°C to +50°C (32°F to 122°F)
Storage Temp.:	-40°C to +70°C (-40°F to 158°F)
Humidity:	Up to 85% Relative humidity Non Condensing
Drop Spec:	Multiple 4ft./1.2m drops to concrete
Sealing:	IP54 when fitted to ET1
Electrostatic Discharge (ESD):	+/-8kV air discharge, +/-4kV direct discharge
ROHS	Complies with Directive 2002/95/EC

Regulatory

Electrical Safety:	IEC 60950-1:2005 (2nd Ed 2005: A1:2009) EN 60950-1:2006+A11:2009+A12:2011 AS/NZS 60950.1:2011 UL 60950-1 (CAN C22.2 CSA 60950-1), 2nd Ed, A1:2011 CAN/CSA-C22 NO. 60950-1-07 (R2012)
EMI/RFI:	Title 47 of the CFR: 2010, Part 15 Subpart (b) – Unintentional Radiators, Class B limits. ICES-003 Issue 5, Class B limits. EN 55022:2010. EN61000-4-2:2009. EN61000-4-3:2006 + A2:2010.

PART NUMBERS

1145-ET1-MSR	1145 Magnetic Swipe Reader for the
	Motorola ET1 Tablet

WARRANTY

The TSL 1145 reader is warranted against defects in workmanship and materials for a period of one year (12 months) from date of shipment, provided the product remains unmodified and is operated under normal and proper conditions.

ABOUT

ABOUT TSL®



Technology Solutions UK Ltd (TSL®), part of HID Global, is a leading manufacturer of high performance mobile RFID readers used to identify and track products, assets, data or personnel.

For over two decades, TSL® has delivered innovative data capture solutions to Fortune 500 companies around the world using a global network of distributors and system integrators. Specialist in-house teams design all aspects of the finished products and software ecosystems, including electronics, firmware, application development tools, RF design and injection mould tooling.

TSL® is an ISO 9001:2015 certified company.



ISO 9001: 2015

CONTACT

Address: Technology Solutions (UK) Ltd, Suite A, Loughborough Technology Centre, Epinal Way,

Loughborough, Leicestershire, LE11 3GE, United Kingdom.

Telephone: +44 1509 238248
Fax: +44 1509 214144
Email: enquiries@tsl.com
Website: www.tsl.com

ABOUT HID GLOBAL



HID Global powers the trusted identities of the world's people, places and things. We make it possible for people to transact safely, work productively and travel freely. Our trusted identity solutions give **people** convenient access to physical and digital **places** and connect **things** that can be identified, verified and tracked digitally. Millions of people around the world use HID products and services to navigate their everyday lives, and billions of things are connected through HID technology. We work with governments, educational institutions, hospitals, financial institutions, industrial businesses and some of the most innovative companies on the planet. Headquartered in Austin, Texas, HID Global has over 4,000 employees worldwide and operates international offices that support more than 100 countries. HID Global is an ASSA ABLOY Group brand.

For more information, visit www.hidglobal.com.

Technology Solutions (UK) Ltd reserves the right to change its products, specifications and services at any time without notice.