



1157 CONTACT SMART CARD READER FOR MOTOROLA MC55/65/67 PRELIMINARY SPECIFICATION



A Snap-on Solution

This accessory for the MC55/65/67 series of terminals provides contact Smart Card functionality. The unit attaches as a snap on to the bottom of the terminal. The mechanical design of the module enables the attachment to remain compatible with existing MC55/65/67 accessories such as the desktop charge cradle.

The USB port from the terminal is brought through to the docking connector on the bottom of the Smart Card snap-on to provide ActiveSync connectivity to the terminal. Charge is passed through to allow the host terminal to be charged without removing the card reader.

Fully Compliant Smart Card Reader

The Smart Card Reader is compliant to ISO7816-1,2,3,4 and supports T=0 and T=1 protocols. A PC/SC compliant driver is provided. The reader is suitable for a wide range of applications across government, enterprise and financial sectors.

The smart card connector meets the requirements of ISO 7816-2 and is rated for a minimum of 500 000 insertion cycles. It uses landing contacts which touch the card only when it is almost fully inserted to minimize card and contact wear.

Features:

One Piece Charging

The reader is powered by the MC55/65/67, and charging is passed through the reader's docking connector to the host terminal

Standards based solution

Compliant to ISO7816-1,2,3,4 and supports T=0 and T=1 protocols

Reader Performance

420 kbits/s to card. Supports embossed cards



1157 PRELIMINARY SPECIFICATION

Physical Characteristics

Dimensions (max):	100mm × 88mm × 35mm
Weight:	108g
Enclosure material:	GE Lexan Polycarbonate
Colour:	Black
Material finish:	Sparked surface

Contact Smart Card Reader

Compliance:	ISO7816-1,2,3,4 T=0, T=1 Protocol 2 wire (SLE 4432/42, S=10), 3 wire (SLE 4418/28, S=9) and I2C (S=8) also supported by reader hardware
Power Source:	MC55/65/67 switched USB 5V output
Current consumption:	Typically 35mA, excluding smart card operating current
Smart Card Clock Frequency	Up to 8MHz
Supported Card Types	5V, 3V and 1.8V Smart Cards ISO7816 Class A, AB and C
Power to Smart Card	60mA

Environmental

Operating Temp.:	-10°C to +50°C
Storage Temp.:	-40°C to +70°C
Humidity:	Up to 95% Relative humidity Non Condensing

Regulatory

Electrical Safety:	TBC
EMC:	TBC
RoHS:	2011/65/EU (RoHS 2) Restriction of the use of certain Hazardous Substances in electrical and electronic equipment 2015/863 (RoHS 3) Amendment to Annex II of 2011/65/EU

PART NUMBERS

1157-SO-MC67-CSC	Smart Card Reader for Motorola MC55/65/67
------------------	---

WARRANTY

The TSL 1157 reader is warranted against defects in workmanship and materials for a period of one year (12 months) from date of shipment, provided the product remains unmodified and is operated under normal and proper conditions.

ABOUT

ABOUT TSL®



Technology Solutions UK Ltd (TSL®), part of HID Global, is a leading manufacturer of high performance mobile RFID readers used to identify and track products, assets, data or personnel.

For over two decades, TSL® has delivered innovative data capture solutions to Fortune 500 companies around the world using a global network of distributors and system integrators. Specialist in-house teams design all aspects of the finished products and software ecosystems, including electronics, firmware, application development tools, RF design and injection mould tooling.

TSL® is an ISO 9001:2015 certified company.



ISO 9001: 2015

CONTACT

Address: Technology Solutions (UK) Ltd, Suite A, Loughborough Technology Centre, Epinal Way, Loughborough, Leicestershire, LE11 3GE, United Kingdom.

Telephone: +44 1509 238248

Fax: +44 1509 214144

Email: enquiries@tsl.com

Website: www.tsl.com

ABOUT HID GLOBAL



HID Global powers the trusted identities of the world's people, places and things. We make it possible for people to transact safely, work productively and travel freely. Our trusted identity solutions give **people** convenient access to physical and digital **places** and connect **things** that can be identified, verified and tracked digitally. Millions of people around the world use HID products and services to navigate their everyday lives, and billions of things are connected through HID technology. We work with governments, educational institutions, hospitals, financial institutions, industrial businesses and some of the most innovative companies on the planet. Headquartered in Austin, Texas, HID Global has over 4,000 employees worldwide and operates international offices that support more than 100 countries. HID Global is an ASSA ABLOY Group brand.

For more information, visit www.hidglobal.com.