

2136 4-SLOT BATTERY CHARGER MULTI-SLOT EASYPACK BATTERY CHARGER











Fast and convenient charging

The 2136 4-Slot Battery Charger is an easy and convenient solution for charging multiple EasyPack™ batteries. It is compatible with both standard 'L' and high capacity 'XL' batteries. Included are two battery retaining clips that can be adjusted in position to accommodate the two sizes of battery.

Multiple configurations

The 2136 4-Slot Battery Charger can be used with many configurations. Either one, two, three or four batteries can be charged at the same time (each row must have identical capacity batteries). The cradle senses the inserted batteries and adjusts its charge rate accordingly. There is an individual charge status LED for each battery slot in addition to a main power supply status LED.

Compatibility

EasyPack batteries are used in the following products:

- 1128 Bluetooth® Handheld UHF RFID Reader (EasyPack™ XL)
- 1153 Bluetooth® Wearable UHF RFID Reader (EasyPack™ L)
- 1119 UHF RFID Reader for the Motorola MC55/65/67 (EasyPack™ L)
- 2128 Bluetooth® Handheld UHF RFID Reader (EasyPack™ XL)
- Honeywell IH21 Bluetooth® Handheld UHF RFID Reader (EasyPack™ XL)
- 2173 Bluetooth® Wearable HF/LF RFID Reader (EasyPack™ L)

The 2136 4-Slot Battery Charger includes a 5.2V, 4A Power Supply unit.

Features:

Quick and Secure Fastening

The retaining clips hold the batteries securely and allow speedy installation and removal.

Small Footprint

The 2136 4-Slot Battery Charger boasts a small footprint enclosure (110 x 110 mm).

Visual Feedback

Individual charge status LEDs for each battery slot in addition to a main power supply status LED.

Excellent Stability

A low profile enclosure combined with grippy rubber feet ensures excellent stability.

Physical Characteristics

Dimensions (max):	110mm (w) × 110mm (d) × 85mm (h)
Dimensions (without battery retainer clips)	110mm (w) × 110mm (d) × 41mm (h)
Weight:	185g (6.5 oz)
Enclosure material:	Polycarbonate
Colour:	Grey with black battery retainer clips.
Material finish:	Sparked surface
User indication:	Individual charge status indicator for each battery slot.

Charging Compatibility

Compatible Power Supply:	5.2V, 4A Power Supply (included)
Compatible Batteries:	EasyPack™ L Rechargeable Li-Polymer battery EasyPack™ XL Rechargeable Li-Polymer battery
Charge time:	Varies depending on the type and number of batteries, typically 75 minutes with a single EasyPack™ L to 180 minutes with four EasyPack™ XL.

Environmental

Operating Temp.:	5°C to 40°C (41°F to 104°F)
Storage Temp.:	-40°C to +70°C (-40°F to 158°F)
Humidity:	Up to 90% Relative humidity Non Condensing
Drop Spec:	76.2cm (30 inch) drops to vinyl tiled concrete at room temperature
Electrostatic Discharge (ESD):	+/-15kV air discharge, +/-8kV direct discharge
Construction:	RoHS compliant

Regulatory

Regions	EU (CE), USA (FCC), Canada
EMC	EN 55032:2015 +AC:2016 EN 55024:2010 +A1:2015 47 CFR Part 15B 15.107, 15.109 ICES-003 Issue 6
Electrical Safety	IEC 62368-1:2014 CB EN 62368-1:2014 +AC:2015 UL 62368-1:2014 CAN/CSA C22.2 No. 62368-1-14
Environmental	2011/65/EU (RoHS 2) Restriction of the use of certain Hazardous Substances in electrical and electronic equipment 2015/863 (RoHS 3) Amendment to Annex II of 2011/65/EU

Warranty

The TSL® 2136 Battery Charger is warranted against defects in workmanship and materials for a period of one year (12 months) from date of shipment, provided the product remains unmodified and is operated under normal and proper conditions.

 $\mathsf{EasyPack}^{^\mathsf{TM}} \ \mathsf{is} \ \mathsf{a} \ \mathsf{trademark} \ \mathsf{of} \ \mathsf{VARTA} \ \mathsf{Microbattery} \ \mathsf{GmbH}$

2136 PART NUMBERS

Product Part Number 4-Slot Battery Charger, including PSU 2136-01-4WMS-CHG

Accessories	Part Number
Spare Battery for 2173 HF/LF RFID Reader	2173-00-BA-1000
Spare Battery for 1153 UHF RFID Reader	1153-00-BA-1000
Spare Battery for 1128/2128 UHF RFID Reader	1128-00-BA-2000
Spare Battery for 1119 UHF RFID Reader	1119-00-BA-1000
Spare Battery for 1062 HF RFID Reader	1062-00-BA-1000

ABOUT

ABOUT TSL®



Technology Solutions UK Ltd (TSL®), part of HID, is a leading manufacturer of high performance mobile RFID readers used to identify and track products, assets, data or personnel.

For over two decades, TSL® has delivered innovative data capture solutions to Fortune 500 companies around the world using a global network of distributors and system integrators. Specialist in-house teams design all aspects of the finished products and software ecosystems, including electronics, firmware, application development tools, RF design and injection mould tooling.

TSL® is an ISO 9001:2015 certified company.



ISO 9001: 2015

CONTACT

Address: Technology Solutions (UK) Ltd, Suite A, Loughborough Technology Centre, Epinal Way,

Loughborough, Leicestershire, LE11 3GE, United Kingdom.

Telephone: +44 1509 238248
Fax: +44 1509 214144
Email: enquiries@tsl.com
Website: www.tsl.com

ABOUT HID



HID powers the trusted identities of the world's people, places and things. We make it possible for people to transact safely, work productively and travel freely. Our trusted identity solutions give **people** convenient access to physical and digital **places** and connect **things** that can be identified, verified and tracked digitally. Millions of people around the world use HID products and services to navigate their everyday lives, and billions of things are connected through HID technology. We work with governments, educational institutions, hospitals, financial institutions, industrial businesses and some of the most innovative companies on the planet. Headquartered in Austin, Texas, HID has over 4,000 employees worldwide and operates international offices that support more than 100 countries. HID is an ASSA ABLOY Group brand.

For more information, visit www.hidglobal.com.

Technology Solutions (UK) Ltd reserves the right to change its products, specifications and services at any time without notice.